




This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED
1		RELEASED FOR PRODUCTION.	12/20/2016	RJC	JAG







NOTE:
REF. AIRBUS T/N 1X56-150-123.

DART AEROSPACE																							
TITLE LOCKING RING																							
DWG NO. RBE1X56-150-124	REV 1																						
<table border="1"> <tr> <td>MAT'L</td> <td>UNLESS OTHERWISE SPECIFIED</td> </tr> <tr> <td>FEAT</td> <td>DIMENSIONS ARE IN INCHES</td> </tr> <tr> <td>TREAT</td> <td>.XXX ± .005 FRACTIONS ± 1/8</td> </tr> <tr> <td>FINISH</td> <td>.XX ± .01 ANGLES ± 5°</td> </tr> <tr> <td></td> <td>.X ± .1 SURFACES = 125°</td> </tr> <tr> <td>SPEC</td> <td>1. BREAK ALL SHARP EDGES .015 x 45° OR .015R</td> </tr> <tr> <td>DRAWN BY:</td> <td>2. DIMENSIONAL LIMITS APPLY AFTER PLATING</td> </tr> <tr> <td>CHECKED:</td> <td>3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009</td> </tr> <tr> <td>OPPS APPR:</td> <td>USED ON MODEL</td> </tr> <tr> <td>QA APPR:</td> <td>EC145</td> </tr> <tr> <td>APPROVED:</td> <td></td> </tr> </table>		MAT'L	UNLESS OTHERWISE SPECIFIED	FEAT	DIMENSIONS ARE IN INCHES	TREAT	.XXX ± .005 FRACTIONS ± 1/8	FINISH	.XX ± .01 ANGLES ± 5°		.X ± .1 SURFACES = 125°	SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R	DRAWN BY:	2. DIMENSIONAL LIMITS APPLY AFTER PLATING	CHECKED:	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	OPPS APPR:	USED ON MODEL	QA APPR:	EC145	APPROVED:	
MAT'L	UNLESS OTHERWISE SPECIFIED																						
FEAT	DIMENSIONS ARE IN INCHES																						
TREAT	.XXX ± .005 FRACTIONS ± 1/8																						
FINISH	.XX ± .01 ANGLES ± 5°																						
	.X ± .1 SURFACES = 125°																						
SPEC	1. BREAK ALL SHARP EDGES .015 x 45° OR .015R																						
DRAWN BY:	2. DIMENSIONAL LIMITS APPLY AFTER PLATING																						
CHECKED:	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009																						
OPPS APPR:	USED ON MODEL																						
QA APPR:	EC145																						
APPROVED:																							
SCALE 1:2	DATE 8/16/2016																						
SHEET 1 OF 6																							

ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
			-1	1	CLAMP HALF #1	WHITE DELRIN/ACETAL		2
			-3	1	CLAMP HALF #2	WHITE DELRIN/ACETAL		3
			-5	1	LOCK	A36/1018/1020 HR		4
			-7	1	LOCKING LEVER	A36/1018/1020 HR		5
			-9	1	BLOCK	A36/1018/1020 HR		6
		B/O	-11	4	DOWEL PIN	STEEL	Ø3 X 30mm {MCMASTER-CARR #91595A134}	1

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED








(-1)

CLAMP HALF #1

DART AEROSPACE	
TITLE LOCKING RING	
DWG NO. RBE1X56-150-124-1	REV 1
MAT'L WHITE DELRIN/ACETAL HEAT TREAT FINISH SPEC	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX \pm .005 FRACTIONS \pm 1/8 .XX \pm .01 ANGLES \pm 5° .X \pm .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	USED ON MODEL
CHECKED: DUERFELDT	EC145
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:2	DATE 8/15/2016
SHEET 2 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED






③

CLAMP HALF #2

DART AEROSPACE			
TITLE LOCKING RING			
DWG NO. RBE1X56-150-124-3			REV 1
MAT'L WHITE DELRIN/ACETAL		UNLESS OTHERWISE SPECIFIED	
HEAT TREAT		DIMENSIONS ARE IN INCHES	
FINISH		.XXX ± .005 FRACTIONS ± 1/8	
SPEC		.XX ± .01 ANGLES ± 5°	
DRAWN BY: CLOUGH		.X ± .1 SURFACES = 125✓	
CHECKED: DUERFELDT		1. BREAK ALL SHARP EDGES	
OPPS APPR: ANDERSON		.015 x 45° OR .015R	
QA APPR: LINDSAY		2. DIMENSIONAL LIMITS APPLY	
APPROVED: GILBERT		AFTER PLATING	
SCALE 1:2		3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DATE 8/15/2016		USED ON MODEL	
SHEET 3 OF 6		EC145	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS			
REV	ECR	DESCRIPTION	DATE






(-5)
LOCK

DART AEROSPACE	
TITLE LOCKING RING	
DWG NO. RBE1X56-150-124-5	REV 1
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2 REV D	.XX ± .01 ANGLES ± .5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
	USED ON MODEL
	EC145
SCALE 2:1	DATE 8/16/2016
	SHEET 4 OF 6

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



(-7)



LOCKING LEVER

NOTE:
USE CAD DATA.

DART AEROSPACE	
TITLE LOCKING RING	
DWG NO. RBE1X56-150-124-7	REV 1
MAT'L A36/1018/1020 HR HEAT TREAT FINISH BLACK OXIDE SPEC QMSI-6.2.2 REV D	
UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES .XXX ± .005 FRACTIONS ± 1/8 .XX ± .01 ANGLES ± 5° .X ± .1 SURFACES = 125°	
1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009	
DRAWN BY: CLOUGH	USED ON MODEL
CHECKED: DUERFELDT	EC145
OPPS APPR: ANDERSON	
QA APPR: LINDSAY	
APPROVED: GILBERT	
SCALE 1:1	DATE 8/16/2016
SHEET 5 OF 6	

This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR.

REVISIONS				
REV	ECR	DESCRIPTION	DATE	INITIAL
				APPROVED



(-9)
BLOCK

DART AEROSPACE	
TITLE LOCKING RING	
DWG NO. RBE1X56-150-124-9	REV 1
MAT'L A36/1018/1020 HR	UNLESS OTHERWISE SPECIFIED
HEAT TREAT	DIMENSIONS ARE IN INCHES
FINISH BLACK OXIDE	.XXX ± .005 FRACTIONS ± 1/8
SPEC QMSI-6.2.2 REV D	.XX ± .01 ANGLES ± .5°
DRAWN BY: CLOUGH	.X ± .1 SURFACES = 125°
CHECKED: DUERFELDT	1. BREAK ALL SHARP EDGES
OPPS APPR: ANDERSON	.015 x 45° OR .015R
QA APPR: LINDSAY	2. DIMENSIONAL LIMITS APPLY
APPROVED: GILBERT	AFTER PLATING
SCALE 2:1	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009
DATE 8/16/2016	USED ON MODEL
SHEET 6 OF 6	EC145